



SE - 406 20/08/28 v.02 RGBs

## OPV - 55

### Offshore Patrol Vessel 55 m

The **Offshore Patrol Vessel 55** is designed by Seatech Engineering Ltd. The main challenge for designing team was creating a vessel able for the following specific functions: patrol operation on costal and international waters; control and surveillance of exclusive economic zone; defending of maritime border, and preventive actions; identification of ships and their accurate position; preventive actions against piracy and maritime terrorism; combating smuggling and immigration control; patrolling/SAR action in co-operation with helicopter; protection of fisheries and marine environment protection; fire fighting at sea; first medical help.

Designed patrol boat is a monohull with the hull of displacement type with V-type fore, raked stem and transom aft. Flat transom stern of the vessel is provided with a lockable hangar for a boarding boat. A helideck, for helicopters weighting up to 4,5 t and having max. length of 16 m, is placed above the main deck. For rolling reduction while helicopter taking off, or landing, two fin stabilizers are provided.

#### Rules and regulations

The ship will comply with all following rules and regulations: Sea going vessels classification and construction rules of acknowledged Classification Society, IMO: COLREG, MARPOL, International Convention on Tonnage Measurement of Ships.

#### Propulsion

2 x MTU 20V4000 M93L each 4300kW at 2100 rpm; 2 x controllable pitch propellers (4 or 5 bleeds), hydraulically controlled, Ø abt. 2,2 m; Bow thruster abt. 95 kW; Generating sets: 3 pcs of 200 kVA, 3 x 400 V, 50 Hz, 1 ps of 100 kVA, 3 x 400 V, 50 Hz.



## OPV - 55

### Offshore Patrol Vessel 55 m

#### Principal characteristics

Length o.a.:	approx.55,00 m
Length b.p.p.:	50,40 m
Breadth moulded:	9,20 m
Breadth at waterline:	8,30 m
Depth to the main deck line:	4,90 m
Draught from base plane:	2,30 m
Draught oa (incl.propeller):	2,80 m
Displacement full:	524 t
Disp. estimated for draught 2,2 m:	460 t
Engine power:	2 x 4300 kW at 2100rpm
Propulsion:	2 controllable pitch propellers
Cruising range:	3000 km
Speed:	16 / 25 kn
Crew:	33 persons

#### Navigation and communication equipment

Radio-communication system will meet GMDSS requirements for the area A1 + A2 + A3: SSB, SATCOM – C complete, 2VHF/DSC radiotelephone system, 1 Navtex receiver, 2 radar transponders, 1 radio VHF for communication with helicopter, Internal LAN network, CCTV. Navigation equipment: 1 magnetic compass with periscope, 1 gyrocompass complete with repeaters, 1 steering control system with autopilot, 1 electromagnetic speed log, 1 echo-sounder, 1 DGPS receiver, 1 GPS receiver with NMEA signal divider, day/night vision system, 2 radars, voyage data recorder (VDR)

#### Deck equipment

electrical hydraulic deck crane 0,52 KN/9,4m, lifting moment 5,8 mt, 4 knuckle capability, boarding boat, dim. 9x3,2 m, for 10 persons, speed 40kn stationary engine, water jet propulsion (on stern slipway), "A-frame" davit for lowering rescue boat, folding railings for protecting deck near helideck, 4 inflatable life rafts each for 25 persons, life-saving appliances corresponding with International Convention and Rules.

#### Artillery armament

One 20–25 mm gun mounting will be installed on the forecastle deck. For gun re control an optical sight will be provided. Gun mounting will be hydraulically powered with electrical control. Abt. 1000 ammunition rounds will be stowed in the ammunition store.

#### Machine guns

Two 12.7 mm machine guns will be fitted on the bridge deck aft. Machine guns will be provided with abt. 2000 ammunition rounds stowed in the ammunition store.

#### Small arms

One separate stowage room for twenty pieces of small arms arranged in the deckhouse on the main deck. Ammunition (abt. 2500 rounds) will be stowed in the ammunition store.